

MRM-72 Dual-Channel Diversity Receiver Module

Introduction

The modular receiver design allows for fast and easy installation or replacement of MIPRO MA-708 and MA-808 portable wireless PA systems. Installation or replacement takes less than a minute.

Key Features

- Advanced diversity technology for optimum reception quality.
- Preset with 16 auto-scanable frequencies.
- One-touch Scan for one of the 16 clear, interference-free frequencies.
- One-touch ACT™ syncs the transmitter and receiver frequency automatically.
- Bright and easy-to-read channel display.
- 5-segment RF and Audio meters.
- Dual "PiloTone & NoiseLock" circuits minimize interference.
- Warning indicator detects potential interference.
- "Sensitivity" adjustor can be adjusted to minimize interference.
- Modular design allows easy installation and replacement.
- When installed, master volume of MA-708 & MA-808 portables can be wirelessly controlled from a distance by a ACT-30Hr handheld transmitter microphone.



Transmitters & Microphones

ACT-30H	Handheld Transmitter
ACT-30T	Bodypack Transmitter

Related

MA-708	Portable Wireless PA System
MA-808	Portable Wireless PA System

Technical Specifications

Frequency Range	UHF 480 ~ 934MHz
Oscillation Mode	PLL synthesized
Bandwidth	24MHz
Preset Channels	16
Receiving Mode	CPU-controlled Diversity Receiving
Squelch Control	"PiloTone & NoiseLock" dual-squelch circuit
Display Status	Channel, RF & audio meters, interference warning indicator & Sensitivity adjustor.
Sensitivity	6dB μ V, at S/N>80dB
Spurious Emissions	<82dB
Frequency Response	60Hz ~ 15KHz (Overall system)
S/N Ratio	>100dBA
T.H.D.	<0.5% @ 1KHz (Dev. =40KHz)
AF Output	610mV rms
Power Supply	12 ~ 15V DC
Current Consumption	<190 mA
Operating Temperature	-10 ~ 60
Dimensions	220(W) x 57(H) x 190(D) mm / 8.7(W) x 2.2(H) x 7.5(D) "
Weight	622g / 22oz



MIPRO Electronics Co., Ltd

Headquarters: 814 Pei-kang Road, Chiayi, 60096, Taiwan
Tel: +886.5.238.0809 | Fax: +886.5.238.0803
www.mipro.com.tw | mipro@mipro.com.tw